

POS TOUCH PC SYSTEM



DS-500 Touch POS PC

The sleek yet economical Touch POS system is built to work in the typical harsh retail, hospitality and food service environments. It is engineered for easy setup, quick serviceability and rigorous use that are characteristics of most POS environments.

With simple access to connectivity for peripherals and built-in open architecture to install any software application, the DS-500 helps lower your total cost of ownership and increases sales efficiency.

Innovation

- Small footprint
- Proven 3-rd generation fanless design
- Enhanced touch screen features
- Ultra fast 10/100/1G integrated network interface
- Standard 3,5" size Hard Drive
- Tool free design for easy servicing
- Uninterruptible power supply

Reliability

- Tested to withstand the punishment POS equipment must endure
- Industrial PC components with long time availability mounted on internal rugged metal frame
- Double back-lighted industrial A grade LCD matrix
- Integrated connectivity ports to ensure no loose cables

Specifications

Processor	Intel Celeron-M 1GHz CPU
Memory	256MB DDR up to 2GB, 2 memory slots
Display	15" Active LCD TFT Color Display
Viewing Angle	0 to 60 degrees tilt
Resolution	800x600, 1024x768
Touch Screen	5-wire resistive or optional capacitive
LCD Brightness	250 nits (w/o touch)
Network	10/100/1G on board Ethernet controller
Storage	1 x 3.5" hard drive
Expansion Options	- Compact flash card socket, IDE interface - 1 mini-PCI
I/O Interfaces	- 1 x parallel port - 4 x RS232 posts, COM3 & 4 provide +5/12V through jumper free BIOS setting - 1 x PS/2 Mouse - 1 x PS/2 KB port - 2 x USB 2.0 ports in rear panel - 2 x USB 2.0 ports on front under cover - 1 x DB-15 VGA port for secondary monitor - 1 x RJ11 24VDC cash drawer port - 2 x Audio ports (1 x Line-out, 1 x MIC-in) - 1 x RS45 LAN port
Operation System	Windows 2000/XP Pro/XPE/CE.Net/WEPOS/Linux
Power Supply	100-240vAC, DC+19V, 90W power adaptor
Temperature	Operating Temperature: 0~40 degrees C Storage Temperature: -20~60 degrees C
Humidity	Operating Humidity: -20% ~85% Storage Humidity: -5%~85%
Dimension	Footprint (WxD): 255 x 275 mm Physical (WxDxH): 340 (385 with MCR) x 275 x 255~350mm (depending LCD angle position)
Weight	10kg
Options	- Dual or three track magnetic card reader - 2x20 VFD customer display - Your logo/brand on front and rear cover - Thermal receipt printer



Adjustable LCD position for comfortable viewing.



Elegant thin frame LCD displaying nice picture.



Rear mounted elegant VFD customer display.



Hidden 2 USB ports and power switch. Status LEDs on front. Your logo/brand optionally.



Rear cover hides cables connectors, but provides free tool access to I/O board and HDD.



Internal metal frame. Enough ports for peripherals. Quick serviceability.